



IP65 high precision scales, suitable for laboratory and industrial use. The completely stainless steel structure makes this scale suitable for the environments with strict hygiene requirements.

Technical Features

- High contrast backlit display.
- Splashproof membrane keypad.
- Splashproof construction, upper structure completely in stainless steel.
- Overall IP65 protection.
- Stainless steel plate, size:
 - GAM320 and GAM820 models \varnothing 140mm
 - GAM2200, GAM3200, GAM6200, GAM8200, GAM15000 models 190x190mm.
- Weight detection through tuning fork system.
- Level and adjustable foot assembly.
- Power supply: standard fitted with 230 Vac power adapter or optional kit for power supply through 4 AA batteries.
- Operating temperature +0°C...+40°C, non-condensing relative humidity 80%.
- RS232/c port for connection to PC, 3590E series indicator or printer.

Standard Functions

- Totalisation.
- Weight checking.
- Counting.
- % weight.
- Suspended weighing (for gravimetric measurements).
- Animals weighing.
- Zeroing.
- Semi-automatic tare.
- Digital calibration.

Available versions

Code	Class	Plate Max (mm)	Max (g)	d (g)	M (g)*	Linearity (g) +/-	Repeatability (g)
GAM320	II	\varnothing 140 mm	320	0,01	0,01	0,01	0,01
GAM820	II	\varnothing 140 mm	820	0,01	0,01	0,01	0,01
GAM2200	II	190x190 mm	2200	0,1	0,1	0,1	0,1
GAM3200	II	190x190 mm	3200	0,1	0,1	0,1	0,1
GAM6200	II	190x190 mm	6200	0,1	0,1	0,1	0,1
GAM8200	II	190x190 mm	8200	0,1	0,1	0,1	0,1
GAM15000	II	190x190 mm	15000	1	1	1	1

