



## Main Features

- LED display: 7 bright red segments with 7 digits, 15 mm high, for viewing the weight and 6 LEDs for showing the active functions.
- Waterproof keypad with 8 functional keys.
- Stainless steel structure.
- Stainless steel plate, 190x220mm size.
- Functions with aluminium "single point" load cell, with anticorrosive treatments.
- Protection from dust and water splashes according to IP65 standards.
- Adjustable feet and level.
- Digital calibration & set-up configurable from keyboard.
- 12 Vdc power supply with an external 230 Vac power adapter.

## Selectable Functions:

- Counting.
- Totalisation / Formulation with management of 3 zeroable and printable totals independent from each other (partial total, general total, grand total).
- +/- Tolerance check.
- Percentage weigh.
- Programmable set point available for all the functioning modes.

## Available versions

Code	Class	Plate Max (mm)	Max (g)	d (g)	Linearity (g) +/-	Repeatability (g)
TRD6500	-	190x220mm	6.500	0,1	0,15	0,1
TRD10K2	-	190x220mm	2.000/10.000	0,1/1	0,2/1	0,1/1

High resolution IP65 stainless steel balances for industrial and laboratory use. Particularly suitable where there are strict hygiene requirements. The dual range models have a higher accuracy on the lower part of the range.

## Keypad Functions:

- Zero, Tare, Print, Mode, On-Off/Clear and 3 navigation keys

## I/O Section:

- RS232/C or TTL bidirectional output for connection to printer or remote display.
- Bi-directional RS232/C or RS485 configurable output for PC, PLC and additional remote display.

