

RCPT SERIES

Analog Column Load Cell



Column load cell for CE-M approved weighbridges, tanks, silos, etc.

CAPACITIES (kg): 20000, 30000, 50000.

OIML R60. C3 precision class.

Technical Features

- Minimum load cell verification interval: $V_{min} = E_{Max} / 10.000$.
- Maximum number of load cell divisions: $n_{LC} = 3000$ (C3).
- Sensitivity: $2mV/V \pm 0.1\%$.
- Temperature effect on full scale: $0.002\% / ^\circ C$.
- Temperature effect on zero: $0.002\% / ^\circ C$.
- Compensated temperature range: $-10^\circ C / +40^\circ C$.
- Operating temperature range: $-30^\circ C / +70^\circ C$.
- Creep error after 30 minutes: 0.02% F.S.
- Excitation voltage from 5 to 15 VDC.
- Input resistance: 700 ± 20 Ohm.
- Output resistance: 703 ± 7 Ohm.
- Zero balance: $\pm 1\%$ F.S.
- Insulation resistance: >5000 MOhm.
- Safe overload: $>150\%$ F.S.
- Ultimate overload: 250% F.S.
- 4-wire shielded cable, 18 m long (or length 20 m for codes -1), 5mm diameter.

Main Features

- C3 precision class.
- Special alloy steel body with stainless steel external casing.
- Manufactured with laser solderings.
- Optimised for parallel connection.
- IP68 protection rating.
- Capacity from 20000 to 50000 kg.
- Shielded 18m connection cable.
- Test certificate available upon request.
- Fitted with self-aligned articulated joints, selfcentering plates and protection washer (version with cups).

ATEX Version

- The CCATEX certificate makes the load cell suitable for use in hazardous areas with protection methods according to: ATEX II 1G Ex ia IIC T6 (Ta $-20 \div +40^\circ C$) TX (Ta $-20 \div +65^\circ C$) Ga ATEX II 1D Ex ta IIIC TX $^\circ C$ (Ta $-20 \div +40^\circ C$) TX $^\circ C$ (Ta $-20 \div +65^\circ C$) Da IP65.
- The certificate includes the manual and the ATEX CE conformity declaration (available in EN, DE, FR, and IT). IMPORTANT: the certificate refers to the single load cell. For systems with more load cells, it is necessary to order one certificate for each load cell.

Wiring Code	
Colour	Function
GREEN	OUTPUT +
WHITE	OUTPUT -
RED	INPUT +
BLACK	INPUT -

Available Versions

Code	Max (kg)
RCPT20C3-1	20000
RCPT30C3-1	30000
RCPT50C3-1	50000



LOAD CELL

QATAR : T : +974 44436750
M : +974 66257037

KSA : T : +966 13 855 5359
M : +966 53 121 8181

E-mail : info@realtechgulf.com
Website : www.realtechgulf.com

REALTECHNOLOGIES
Equipments Supply & Service

